

## 210 Gallon Water Storage Tank #210D603723 and 210D603723-B

Will go through a 24" door and fit in a closet or a crawl space



Water storage tanks are available with access lid, vacuum/pressure relief valve and ¼ turn boiler drain. Unfitted tanks measure 23.5" x 37" x 60" and can be configured for use in three orientations: Vertical – 60"H, Horizontal – 37"H and Low Horizontal – 23.5"H. Tanks are made of virgin LLDPE resin meeting FDA regulation 21 CFR 177.1520 © 3.1 & 3.2, for use in storing potable water. The finished product is a one piece seamless tank with 1½" radius inside corners for easy cleaning and walls that are 3/8" thick. Available in Natural White

translucent so water level can be seen or opaque Black for use with waters having Iron or Sulfur bacteria slime problems.

Blind insert attachment points for 8-32, 10-24, ¼"-20, 5/16-18 and 3/8"-16 machine screws and bolts can be spin welded into these tanks.

Flat sided tanks require a frame to maintain their shape when used in the vertical and horizontal orientation. Tanks in these orientations have welded beads at all four sides to indicate where the support frame members are to be installed and prevent the installed frame from sliding out of place. When used in the low horizontal orientation no frame is required.

See page 2 for information on frames and manifolds for putting tanks together to increase storage capacity

Available Through:

Made in the **USA** by Reid Plumbing Products, LLC  
Hopewell, NJ

800-211-8070 from US and Canada.

Elsewhere +1 609-466-4347

[www.wellmanager.com](http://www.wellmanager.com)

***The water you need and  
The performance you want***

Tank Frames are made of 1 5/8" plated Unistrut members held together by 3/4" galvanized schedule 40 steel pipe and plated 3/8" threaded rod.

**Vertical tanks:** FK-2436 consists of two 4 sided frame sets to fit the 23 1/2" x 37" dimension

**Adding vertical tanks:** FK-2436-2 consists of two 3 sided frames designed fasten a second tank to one that already has a 4 sided frame.

**Horizontal tanks:** FK-2460 consists of two 4 sided frames to fit the 23.5" x 60" dimension

**Adding horizontal tanks:** FK-2460-2 consists of two 3 sided frames to fasten additional tanks to one that already has a 4 sided frame.

The ends of the Unistrut side rails are closed using PS655 end caps. Unistrut frame rails can be used to mount control boards, filters, UV Appliances and many other accessory items or as attachment points for pipes using standard Unistrut accessories.

### Increase Storage by Connecting Several Tanks Together Using Frame Kits and Manifold Kits



UPC1P manifold kit includes supports shown  
One kit connects 2 tanks. Buy 1/2 kit to add a single tank  
To 2 existing tanks